


	<p>Pointer N-1</p>	<table border="1"> <tr> <td>Protection class:</td> <td>IP66</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Admissible ambient temperature:</td> <td colspan="5">t_a 40 °C</td> </tr> <tr> <td>Insulation class:</td> <td colspan="5">I</td> </tr> <tr> <td>Marks:</td> <td></td> <td colspan="4">II 3GD EEx nA II T4</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Power supply:</td> <td colspan="5">230 V, 50 Hz</td> </tr> </table>	Protection class:	IP66					Admissible ambient temperature:	t_a 40 °C					Insulation class:	I					Marks:		II 3GD EEx nA II T4										Power supply:	230 V, 50 Hz				
Protection class:	IP66																																					
Admissible ambient temperature:	t_a 40 °C																																					
Insulation class:	I																																					
Marks:		II 3GD EEx nA II T4																																				
Power supply:	230 V, 50 Hz																																					
	<p>Vipet N-1</p>	<table border="1"> <tr> <td>Protection class:</td> <td>IP66</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Admissible ambient temperature:</td> <td colspan="5">t_a 40 °C</td> </tr> <tr> <td>Insulation class:</td> <td colspan="5">I</td> </tr> <tr> <td>Marks:</td> <td></td> <td colspan="4">II 3GD EEx nA II T4 - T5</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Power supply:</td> <td colspan="5">230 V, 50 Hz</td> </tr> </table>	Protection class:	IP66					Admissible ambient temperature:	t_a 40 °C					Insulation class:	I					Marks:		II 3GD EEx nA II T4 - T5										Power supply:	230 V, 50 Hz				
Protection class:	IP66																																					
Admissible ambient temperature:	t_a 40 °C																																					
Insulation class:	I																																					
Marks:		II 3GD EEx nA II T4 - T5																																				
Power supply:	230 V, 50 Hz																																					
	<p>Rambo</p>	<table border="1"> <tr> <td>Protection class:</td> <td>IP42 (IP67)</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Admissible ambient temperature:</td> <td colspan="5">t_a 30 °C</td> </tr> <tr> <td>Insulation class:</td> <td colspan="5">I</td> </tr> <tr> <td>Marks:</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Power supply:</td> <td colspan="4"></td> <td>230 V, 50 Hz</td> </tr> <tr> <td></td> <td colspan="4"></td> <td>24 V, 50 Hz</td> </tr> </table>	Protection class:	IP42 (IP67)					Admissible ambient temperature:	t_a 30 °C					Insulation class:	I					Marks:						Power supply:					230 V, 50 Hz						24 V, 50 Hz
Protection class:	IP42 (IP67)																																					
Admissible ambient temperature:	t_a 30 °C																																					
Insulation class:	I																																					
Marks:																																						
Power supply:					230 V, 50 Hz																																	
					24 V, 50 Hz																																	
	<p>Rambo N</p>	<table border="1"> <tr> <td>Protection class:</td> <td>IP67</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Admissible ambient temperature:</td> <td colspan="5">t_a 40 °C</td> </tr> <tr> <td>Insulation class:</td> <td colspan="5">I</td> </tr> <tr> <td>Marks:</td> <td></td> <td colspan="4">II 3GD; EEx nA II T5</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Power supply:</td> <td colspan="5">230 V, 50 Hz</td> </tr> </table>	Protection class:	IP67					Admissible ambient temperature:	t_a 40 °C					Insulation class:	I					Marks:		II 3GD; EEx nA II T5										Power supply:	230 V, 50 Hz				
Protection class:	IP67																																					
Admissible ambient temperature:	t_a 40 °C																																					
Insulation class:	I																																					
Marks:		II 3GD; EEx nA II T5																																				
Power supply:	230 V, 50 Hz																																					

	<p>Aqua N</p>	<table border="1"> <tr> <td>Protection class:</td> <td>IP67</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Admissible ambient temperature:</td> <td colspan="5">t_a 40 °C</td> </tr> <tr> <td>Insulation class:</td> <td colspan="5">I</td> </tr> <tr> <td>Marks:</td> <td></td> <td colspan="4">II 3GD; EEx nA II T5</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Power supply:</td> <td colspan="5">230 V, 50 Hz</td> </tr> </table>	Protection class:	IP67					Admissible ambient temperature:	t_a 40 °C					Insulation class:	I					Marks:		II 3GD; EEx nA II T5										Power supply:	230 V, 50 Hz				
Protection class:	IP67																																					
Admissible ambient temperature:	t_a 40 °C																																					
Insulation class:	I																																					
Marks:		II 3GD; EEx nA II T5																																				
																																						
Power supply:	230 V, 50 Hz																																					
	<p>Rambo Ex</p>	<table border="1"> <tr> <td>Protection class:</td> <td>IP67</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Admissible ambient temperature:</td> <td colspan="5">t_a 40 °C</td> </tr> <tr> <td>Insulation class:</td> <td colspan="5">I</td> </tr> <tr> <td>Marks:</td> <td></td> <td colspan="4">II 2GD; EEx edm IIC T5</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Power supply:</td> <td colspan="5">230 V, 50 Hz</td> </tr> </table>	Protection class:	IP67					Admissible ambient temperature:	t_a 40 °C					Insulation class:	I					Marks:		II 2GD; EEx edm IIC T5										Power supply:	230 V, 50 Hz				
Protection class:	IP67																																					
Admissible ambient temperature:	t_a 40 °C																																					
Insulation class:	I																																					
Marks:		II 2GD; EEx edm IIC T5																																				
																																						
Power supply:	230 V, 50 Hz																																					
	<p>Aqua Ex</p>	<table border="1"> <tr> <td>Protection class:</td> <td>IP67</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Admissible ambient temperature:</td> <td colspan="5">t_a 40 °C</td> </tr> <tr> <td>Insulation class:</td> <td colspan="5">I</td> </tr> <tr> <td>Marks:</td> <td></td> <td colspan="4">II 2GD; EEx edm IIC T5</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Power supply:</td> <td colspan="5">230 V, 50 Hz</td> </tr> </table>	Protection class:	IP67					Admissible ambient temperature:	t_a 40 °C					Insulation class:	I					Marks:		II 2GD; EEx edm IIC T5										Power supply:	230 V, 50 Hz				
Protection class:	IP67																																					
Admissible ambient temperature:	t_a 40 °C																																					
Insulation class:	I																																					
Marks:		II 2GD; EEx edm IIC T5																																				
																																						
Power supply:	230 V, 50 Hz																																					
	<p>Pitbul Ex</p>	<table border="1"> <tr> <td>Protection class:</td> <td>IP65</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Admissible ambient temperature:</td> <td colspan="5">t_a 40 °C</td> </tr> <tr> <td>Insulation class:</td> <td colspan="5">I</td> </tr> <tr> <td>Marks:</td> <td></td> <td colspan="4">II 2GD; EEx edm IIC T5</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Power supply:</td> <td colspan="5">230 V, 50 Hz</td> </tr> </table>	Protection class:	IP65					Admissible ambient temperature:	t_a 40 °C					Insulation class:	I					Marks:		II 2GD; EEx edm IIC T5										Power supply:	230 V, 50 Hz				
Protection class:	IP65																																					
Admissible ambient temperature:	t_a 40 °C																																					
Insulation class:	I																																					
Marks:		II 2GD; EEx edm IIC T5																																				
																																						
Power supply:	230 V, 50 Hz																																					
	<p>Boxer</p>	<table border="1"> <tr> <td>Protection class:</td> <td>IP54</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Admissible ambient temperature:</td> <td colspan="5">t_a 25 °C</td> </tr> <tr> <td>Insulation class:</td> <td colspan="5">I</td> </tr> <tr> <td>Marks:</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td colspan="5">IK 10 acc. CSN EN 50102</td> </tr> <tr> <td>Power supply:</td> <td colspan="5">230 V, 50 Hz</td> </tr> </table>	Protection class:	IP54					Admissible ambient temperature:	t_a 25 °C					Insulation class:	I					Marks:							IK 10 acc. CSN EN 50102					Power supply:	230 V, 50 Hz				
Protection class:	IP54																																					
Admissible ambient temperature:	t_a 25 °C																																					
Insulation class:	I																																					
Marks:																																						
	IK 10 acc. CSN EN 50102																																					
Power supply:	230 V, 50 Hz																																					

